



ELECTRICAL:

- 1. VOLTAGE RATING : 125 VAC RMS.
- 2. CURRENT RATING : 1.5 AMP.
- 3. CONTACT RESISTANCE : 20 MILLIOHMS MAX.
- 4. INSULATION RESISTANCE : 1000 MEGOHMS MIN @ 500 VDC
- 5. DIELECTRIC STRENGTH : 1000 V AC OR 1500V DC RMS @ 0.5mA 50 Hz / 60 Hz 1 Minute

MECHANICAL:

- 1. HOUSING&INSERT& MATERIAL : PBT UL94V-0.
- 2. CONTACT MATERIAL : PHOSPHOR BRONZE Ø0.46mm.
- 3. PLATING : GOLD PLATING OVER NICKEL.
- 4. OPERATING LIFE : 750 CYCLES MIN.
- 5. MATING/UNMATING FORCE: : 30N Max.
- 6. RETENTION STRENGTH: : 50N FOR 60S±5S.

ENVIRONMENTAL:

- 1. STORAGE : -40°C TO +85°C RELATIVE HUMIDITY<80%.
- 2. OPERATION : -40°C TO +85°C.

MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.

**Part Code: JP- S2 - 10P10C S**

**Description: RJ48 10P10C modular jack with shield**

PRAN ELECTRONICS PVT. LTD.  
 INDIA  
 Rev. 01 date 27/1/2014  
 DRAWING NOT TO SCALE