



ELECTRICAL:

- 1. VOLTAGE RATING : 125 VAC RMS.
- 2. CURRENT RATING : 1.5 AMP.
- 3. CONTACT RESISTANCE : 20 MILLIOHMS MAX.
- 4. INSULATION RESISTANCE : 1000 MEGOHMS MIN @ 500 VDC
- 5. DIELECTRIC STRENGTH : 1000 V AC OR 1500V DC RMS @ 0.5mA 50 Hz / 60 Hz 1 Minute

MECHANICAL:

- 1. HOUSING&INSERT& MATERIAL : PBT UL94V-0.
- 2. CONTACT MATERIAL : PHOSPHOR BRONZE ∅0.46mm.
- 3. PLATING : GOLD PLATING OVER NICKEL.
- 4. OPERATING LIFE : 750 CYCLES MIN.
- 5. MATING/UNMATING FORCE: : 30N Max.
- 6. RETENTION STRENGTH: : 50N FOR 60S±5S.

ENVIRONMENTAL:

- 1. STORAGE : -40°C TO +85°C RELATIVE HUMIDITY<80%.
 - 2. OPERATION : -40°C TO +85°C.
- MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.

Part Code: JP-S2-8P8C-2P

Description: RJ45 8P8C 2Port Short body modular jack

**PRAN ELECTRONICS PVT. LTD.
INDIA
Rev. 00 date 06/04/2019
DRAWING NOT TO SCALE**